



| ITEM | QTY. | UNIT | DESCRIPTION | DRAWING |
|------|------|------|-------------|---------|
|------|------|------|-------------|---------|



PLAN VIEW

NOTE:
FOR MAXIMUM STABILITY, IT
IS RECOMMENDED THAT A
TRIPOD LEG BE POINTED IN
DIRECTION OF FLOW.

| | | | | | | | |
|---|------|----------|--|-------------------|------------------|---------------------------------|------|
| A | DB | 10/18/05 | Released | | | | 8424 |
| REV. | INT. | DATE | CHANGES | | | | ECO# |
| FO No. FAD | | | TITLE TRIPOD INSTALLATION | | | | UNIT |
| DIST. STANDARD | | | | | | | |
| USER | | | | | | | EA |
| <div><div>AUTOMATED</div><div></div><div>CONVEYOR SYSTEMS,INC.</div><div>WEST MEMPHIS, ARKANSAS</div></div> | | | TOLERANCES: DECIMAL ±0.03125", ANGULAR ±1° UNLESS OTHERWISE SPECIFIED | | DATE 10/18/05 | NEXT ASSEMBLY A19601-00-000H | |
| | | | DESIGNED BY: | CHECKED BY: DATE | SCALE 1"=1" | DRAWING NUMBER | |
| | | | DRAWN BY: D.BULONE | APPROVED BY: DATE | REV. A | FAD-141 | |